

New Launch



SA5062
6¹/₂ Digital Multimeter

Features

- Real 6 1/2 digits reading resolution (1199999 counts)
- True-RMS AC Voltage and AC Current measuring
- 4.3-inch color LCD touch screen with double display for easy viewing
- Multi display - Number, Bar, Chart, Histogram

Specification

Basic Function	Range	Best Accuracy ± (% reading + % range)
DC Voltage	100 mV/1 V/10 V/100 V/1000 V	± (0.0035 % + 0.0005 %)
AC Voltage	100 mV/1 V/10 V/100 V/1000 V	± (0.06 % + 0.04 %)
DC Current	100 μA/1 mA/10 mA/100 mA/1 A/10 A	± (0.05 % + 0.006 %)
AC Current	100 μA/1 mA/10 mA/100 mA/1 A/10 A	± (0.1 % + 0.04 %)
Resistance	100 Ω/1 KΩ/10 KΩ/100 KΩ/1 MΩ/10 MΩ/100 MΩ	± (0.01 % + 0.001 %)
Capacitance	1 nF/10 nF/100 nF/1 μF/10 μF/100 μF	± (0.9 % + 1 %)
Frequency	3 Hz ~ 1 MHz	± 0.02 %
Temp	PT100/PT385/PT3916	N/A
Tcouple	K/J/R	N/A
Diode	10 V	N/A
Continuity	1 KΩ	N/A

Features	
Reading Rate	10K reading/s
Auto Range	•
Null	•
Trigger	•
Store/Recall	• 4GB
Math	MAX/MIN, Rel, dB, dBm, Limit, Statistic

General Characteristics	
Safety	IEC61010-1: 2001, CAT I 1000V/CAT II 600V, Class of pollution: 2
Interface	USB Host, USB Device, RS-232, LAN, GBIP (optional)
Power	110 V/220 V (1±10%), 50 Hz/60 Hz, 15 VA
Dimension & Weight	375x260x106 mm, 3.0 kg

Standard Accessories

Power Cord	1	Temperature Probe	1
Test Lead Kit	1	CD	1



ASRAS CO.,LTD
1694, 1694/1 Prachasongkhro Road
Dingdaeng, Dindaeng, Bangkok 10400
Tel. 02-277-9969-70
E-mail : sales@asras.co.th
Website : www.asras.co.th

* Our company reserves the right to change the specification of the catalogue without notice