

Luxmeter LM37

Einsatzprofil

Ideal zur Kontrolle der Lichtverhältnisse an Arbeitsplätzen, Lagerhallen, Industrie- und Wohngebäuden. Z.B. zur Einhaltung der ausreichenden Beleuchtung im Büro oder Arbeitsbereich.

Produktmerkmale

- Großer Messbereich 0,00...40000lx bzw. 0,000...4000fc
- Automatische und manuelle Bereichsumschaltung
- Auflösung 0,01lx bzw. 0,001fc
- Messrate 2 mal pro Sekunde
- Automatische Nullpunkt-Kalibrierung
- Data-Hold Funktion
- Einfache Einhandbedienung

Application profile

Perfectly designed for checking light levels at working places, industrial and private environments and applications of photographic studios.

Product features

- Wide range 0,00...40000lx / 0,000...4000fc
- Automatic/manual selection of range
- Display resolution 0,01lx / 0,001fc
- Measuring interval 500 ms
- Automatic zero adjustment
- Data-Hold function
- Easy to use

lx

BACKLIGHT



5020-0337

Technical data

Measuring range:	0,00 .. 40.000 lx or 0,000 .. 4000 fc
Resolution:	0.01 lx / 0,001 fc
Accuracy:	±3% + 5 Digits
Work temperature:	0°C ... +40°C
Battery life:	typical 24 hrs at continuous use
Power supply:	9 V battery
Dimensions:	33 x 54 x 196 mm (L x W x H)
Weight:	180 g

5020-0337

Lightmeter LM37



ASRAS CO.,LTD
1694, 1694/1 Prachasongkhro Road Dingdaeng,
Dindaeng, Bangkok 10400
Tel. 02-277-9969
E-mail : sales@asras.co.th
Website : www.asras.co.th

Distribution in Thailand by ASRAS Co.,Ltd.