

Introduction

High Voltage Detectors (HVD's) are widely used throughout the electricity industry to determine that high voltage lines are de-energised prior to work being carried out thus ensuring safety of personnel. Designed to comply with relevant IEC standards, HVD's are available for use on system voltages up to 275kV.



HVD Kit

Each HVD standard kit comprises the following components housed within a purpose designed ABS heavy duty carry case;

- High Voltage Detector (HVD)
- Contact electrodes (Y and Hook)
- Rod adaptor
- Polymer cleaning kit
- Instruction Manual

A complete range of accessories is shown overleaf and various carry cases are available depending on the configuration required.

Operation & Features

HVD's are battery operated electronic contact devices that give clear indication of the status of the line under test both visually, by means of super-bright LED's and audibly with a high intensity buzzer. This ensures clear indication even in conditions of bright sunlight and high background noise. The voltage setting to trigger activation (or threshold setting) can be set in accordance with IEC standards or in consultation with the user where detectors are used on a range of system voltages. All detectors have the facility to self check before and after use.




A wide range of models are available to cover most distribution and transmission voltages used throughout the world.

Features

- Automatic alarming above threshold voltage as default
- Easy to use and Lightweight (0.6kg)
- Lightweight (600g)
- Fast response time , less than 1 second
- High Impact ABS body
- Self test facility
- Indoor/Outdoor use
- -25°C to +55°C operating temp range
- Shock & drop resistant
- Standard safety yellow (other colours available)
- Various rod adaptors available to suit different operating rod styles
- Wide range of accessories
- Easy access for battery replacement



Overhead Line Testing



HVD LED Indication



High Voltage Detectors (HVD's)
 Visual Indication (Safe Condition) Green LED flashes at 2Hz
 Voltage Present (Alarm Condition) Red LED flashes at 2Hz
 and Buzzer sounds with 3.1kHz tone, modulated at -70dBA at 1.5m
 Response Time: <1second
 Battery: 9v PP3-C IEC 6LF22



Rod Adaptors
 Rod Adaptors are available for connecting to various operating poles shown from left to right are Bowthorpe, KP (Karl Pfisterer) and Universal Starwheel types



Contact Electrodes
 Three sizes of aluminium hook are available in 40, 60 and 100mm, alternatively a straight 40mm stainless steel stud electrode, or a Y contact electrode can be supplied



Contact Electrode Extensions
 To distance the detector away from any source of interference four sizes of electrode extension are available in 100, 250, 650 and 1000mm



Proving Unit
 In addition to the self test facility an external battery operated proving unit is available to check the completely assembled kit (threshold voltage dependent)
 Output Voltage: 1100v P to P ±100v into a 20MΩ load

<p>High Voltage Instruments Ltd policy is one of continuous development and hence we reserve the right to change specification / design without prior notice</p>	<p style="text-align: center;">High Voltage Instruments Ltd</p> <p style="text-align: center;">1 Wellfield Court Ibrox Business Park Glasgow, G51 2JR UK</p> <p style="text-align: center;">Tel: +44(0)141 440 5800 Fax: +44(0)141 404 2561</p> <p style="text-align: center;">web: www.hvil.co.uk e-mail: sales@hvil.co.uk</p>